Server Routing is in the Consumer's Interest

December 5, 2008

Viable, Inc.

www.viable.net

contact@viable.net



Current Situation

- The June 24, 2008 *Internet-based TRS Numbering Order* states that by December 31, 2008 TRS providers shall:
 - Provision to the central database the direct-device IP address of each of its clients
 - Ensure that all CPE devices are capable of communicating directly with each VRS provider without the need for any intervening server
- Part of the rationale for direct-device routing:
 - Simplified and efficient call setup process
 - Security vulnerabilities stemming from domain names in VRS URIs
 - Improved privacy
 - Speculation that a TRS provider might block or degrade calls

Comparison of Routing Options

Direct-Device Routing

Direct connection between CPE devices

No

No

No impact

No flexibility for future development

What is it?

Uses Proxy Numbers?

Uses DNS in URI request?

e911 call handling?

Promotes development of technology?

Server Routing

Connects CPE devices through a server

No

No

No impact

features without modifications to CPE devices

Minimal Changes

- NeuStar's centralized database already supports Server Routing; no major architecture change would be needed
- With Server Routing, TRS Providers would simply publish the Server's IP address instead of the Client's IP address:

```
BEFORE: phone_number@Client_IP
(2024139213@68.12.125.112)
```


```
AFTER: phone_number@Server_IP
(2024139213@128.121.23.31)
```

Direct-Device Routing will adversely impact consumer experience


- Consumers will be restricted to one CPE device per location
 - Forces sharing of phone number
 - Deprives choice of personal phone line
- Or, Consumers will have to bear extra costs for additional Internet lines/addresses
 - Additional expense in exchange for basic phone features
 - Creates hardship for households where multiple communication modes necessitate multiple devices

Direct-Device Routing


(limited to single CPE device)



Server Routing (allows multiple CPE Devices)




If Consumers want multiple CPE devices



Direct-Device Routing complicates firewall traversal

- Easy setup will not be possible:
 - "Plug and Play" CPE devices will no longer function
 - NAT/firewall router will require configuration for each CPE device
 - Consumers will be unable to bring videophones to alternative locations without complicated setup, limiting the mobility of their CPE devices
 - e.g. hospitals, hotels, public Internet access points
- TRS Providers may pressure Consumers into using their router and selecting them as their default provider



Comparison of Burden to the TRS Fund

Direct-Device Routing

Requires implementation of H.323 stack protocol on CPE Devices

Yes, need to provide pre-configured NAT Router

Yes, some features will be disabled and port-forwarding is complicated

Yes, self-installation will not be feasible

Retrofit CPE devices?

Provide additional equipment to consumers?

Perform additional consumer outreach & education?

Undertake complex CPE device distribution?

Server Routing

Not needed

No, devices will be plug-and-play

No, features will function as they always have

Intuitive setup will make Home installation optional

Server Routing enables services, features and protections

- Multiple locations
- Multiple device logins
- Multiple devices per household
- Video mail
 - Videomail logic and storage are housed on VRS Provider's server, and will be disabled with direct-device routing.
- Consumer call routing preferences
 - Ability to modify universal settings across multiple devices will not be possible
- Is consistent with Section 225(d)(2)
 - The Commission has the obligation to ensure that TRS regulations encourage, not impair, the development of new technology

Server Routing addresses all concerns

- "Simplified, and more efficient, call setup process"
 - Server Routing is equally effective and is also a one-step query
- "Domain names in VRS URIs would introduce security vulnerabilities"
 - Server Routing uses Server IP addresses, <u>not</u> Domain Names
- Compromised privacy
 - CPNI rules are more protective and can be enacted for specific situations
- Speculation that TRS providers might block calls or degrade video quality
 - Anticompetitive behaviors are clearly defined in the Interoperability Requirement

Conclusion

- Direct-Device Routing is technologically regressive
- Allowing Server Routing is in the Consumer's interest
 - Enables firewall-friendly setup and simplified interoperability
 - Is backward-compatible
 - Enables services, features and protections
 - Will spur continued innovation
 - Resolves existing issues without creating new ones
 - Promotes competition
 - Consumers retain use of multiple devices
 - Consumers retain choice of TRS provider